



Quality Pooling Specification Package

September 1, 2018

Table of Contents

Premium Synthetic (PSY) Pool Quality Specifications	1
Synthetic Sweet Blend (SYN) Pool Quality Specifications	2
Hardisty Synthetic Crude (HSC) Pool Quality Specifications.....	3
Condensate Blend (CRW) Pool Quality Specifications.....	4
Mixed Sweet Blend (MSW) Pool Quality Specifications	5
Light Sour Blend (LSB) Pool Quality Specifications	6
Medium Sour Blend (MSB) Pool Quality Specifications	7
Midale (M) Pool Quality Specifications.....	8
Premium Conventional Heavy (PCH) Pool Quality Specifications	9
Conventional Heavy (CHV) Pool Quality Specifications	10
Kearl Heavy Dilbit (KDB) Pool Quality Specifications.....	11
Synbit Blend (SYB) Pool Quality Specifications	12

Premium Synthetic (PSY) Pool Quality Specifications

Quality Specifications for Component Streams to the Premium Synthetic (PSY) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex-Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality
Existing Specifications								
Density (15C)	kg/m ³	>799	<876	830-876...	863	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4:1} @ 37.8 C)	kPa		95 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical								
Sulphur, total	wt%			<0.2	0.1	ASTM D4294	Frequency: AR ²	Notification Process ⁶
Naphtha (IBP-350F)	mass% recovered			8-24	13	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Distillate (350-650F)	mass% recovered			52-70	50	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Gas Oil (650-980F)	mass% recovered			20-30	34	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Resid (+980F)	mass% recovered			<1		ASTM D7169	Frequency: MR ³	Notification Process ⁶
Particulates	ppm			≤20		ASTM D5452-08		
Butane	vol%			≤3		ASTM D7169		
Other Requirements								
<ul style="list-style-type: none"> Stream must be produced by an Upgrader Cetane index in distillate: min 40 								

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

***This specification was revised March 5th, 2014.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of PSY component streams tested using weekly composite.
- MR: Monthly Random testing of PSY component streams.
- QR: Quarterly Random testing of PSY component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018

Synthetic Sweet Blend (SYN) Pool Quality Specifications

Quality Specifications for Component Streams to the Synthetic Sweet Blend (SYN) Pool***								
Quality	Units	Min	Max	Typical*	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications								
Density (15C)	kg/m ³	>799	<876	850-875	862	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8C)	kPa		95 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical****								
Sulphur, total	wt%			0.12-0.21	0.2	ASTM D4294	Frequency: AR ²	Notification Process ⁶
Naphtha (IBP-350F)	mass% recovered			11-18	14	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Distillate (350-650F)	mass% recovered			37-48	45	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Gas Oil (650-980F)	mass% recovered			37-49	38	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Particulates	ppm			0-10		ASTM D5452-08	Frequency: AR ²	Notification Process ⁶
C4-	vol%			1.5-3.5		ASTM D2887		
Other Requirements								
● Stream must be produced by an Upgrader								

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

***SYN (Synthetic Sweet Blend) is the pool name (transport commodity) effective May 1st. SSP (Syncrude Sweet Premium) is a receipt commodity name that will replace the former SYN (Syncrude) as the receipt commodity.

****Component Typical changes on February 27, 2014: Butane changed to C4- and residual typical removed.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of SYN component streams tested using weekly composite.
- MR: Monthly Random testing of SYN component streams.
- QR: Quarterly Random testing of SYN component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018

Hardisty Synthetic Crude (HSC) Pool Quality Specifications

Quality Specifications for Component Streams to the Hardisty Synthetic Crude (HSC) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex-Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications								
Density (15C)	kg/m ³	>799	<876	813-876	863	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8 C)	kPa		95 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical								
Sulphur, total	wt%			<0.2	0.15	ASTM D4294	Frequency: AR ²	Notification Process ⁶
Naphtha (IBP-350F)	mass% recovered			8-30	12	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Distillate (350-650F)	mass% recovered			42-52	44	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Gas Oil (650-980F)	mass% recovered			19-50	41	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Resid (+980F)	mass% recovered			<1		ASTM D7169	Frequency: MR ³	Notification Process ⁶
Other Requirements								
<ul style="list-style-type: none"> Stream must be produced by an Upgrader 								

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of HSC component streams tested using weekly composite.
- MR: Monthly Random testing of HSC component streams.
- QR: Quarterly Random testing of HSC component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018

Condensate Blend (CRW) Pool Quality Specifications

Quality Specifications for Component Streams to the Condensate Blend (CRW) Pool						
Quality	Units	Min	Max	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications						
Density (15C)	kg/m ³	600	775	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁵
Viscosity (@ 7.5C)	cSt		2	ASTM D7042	Frequency: R ⁶	Delayed shut-in ⁵
Olefins, total ¹	mass%		<1	H NMR	Frequency: R ⁶	Immediate shut-in ⁴
Vapour Pressure (DVPE)	kPa		103	ASTM D5191	Frequency: MR ³	Immediate shut-in ⁴
S&W	vol%		0.5	ASTM D4007	Frequency: AR ²	Immediate shut-in ⁴
Organic Chlorides ¹	wppm		<1	ASTM D4929	Frequency: R ⁶	Immediate shut-in ⁴
Sulphur, total	wt%		0.5	ASTM D4294	Frequency: AR ²	Reclassification Process ⁵
Micro Carbon Residue (MCR)	wt%		0.5	ASTM D4530	Frequency: MR ³	Delayed shut-in ⁵
Aromatics, total (BTEX)	vol%	2		PONAOX(U) ASTM D6729	Frequency: R ⁶	Delayed shut-in ^{5,9}
Mercaptans, volatile (cumulative C1, C2, C3)	ppmw S		175	ASTM D5623	Frequency: R ⁶	Delayed shut-in ⁵
H ₂ S (in liquid phase)	wppm		20	ASTM D5623	Frequency: R ⁶	Delayed shut-in ⁵
Benzene ⁷	vol%		1.6	PONAOX(U) ASTM D6729	Frequency: R ⁶	Delayed shut-in ⁵
Mercury ¹	wppb		10	ASTM D7623	Frequency: R ⁶	Monitoring Process ⁸
Oxygenates	wppm		100	PONAOX(U) ASTM D6729	Frequency: R ⁶	Delayed shut-in ⁵
Filterable Solids	wppm		200	ASTM D4807 with "Procedure C"	Frequency: R ⁶	Delayed shut-in ⁵
Phosphorus, volatile	ppm	Per CAPP Guidelines		ICP AES D86 (250 cut)	Frequency: R ⁶	CAPP Guidance. Refer to AEB Directive 058. Violating test results communicated to the AEB

Notes

- For these properties, blending should not occur.
- AR: All Receipts of CRW component streams tested using weekly composite.
- MR: Monthly Random testing of CRW component streams.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random composite testing per CRW component stream. 2015 – Twice per year; 2016 onwards – Annually.
- Benzene level of the CRW pool to be monitored. Results ≥ 1.25 vol% require Enbridge CRW Committee to reconvene appropriateness of benzene spec on CRW component streams
- Monitoring and reporting only.
- For BTEX values < 2.0 vol%, a component stream condensate can still be accepted through completion of a Wiehe compatibility analysis.

Mixed Sweet Blend (MSW) Pool Quality Specifications

Quality Specifications for Component Streams to the Mixed Sweet Blend (MSW) Pool						
Quality	Units	Min	Max	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications						
Density (15C)	kg/m ³	>799	<876	ASTMD4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20	ASTMD7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1	H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4:1} @ 37.8 C)	kPa		95 ⁸	ASTMD6377	Frequency: MR ³	Immediate shut-in ⁵
S&W	vol%		0.5	ASTMD4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1	ASTMD4929	Frequency: QR ⁴	Immediate shut-in ⁵
Sulphur, total	wt%		0.5	ASTMD4294	Frequency: AR ²	Reclassification Process ⁶
Phosphorus, volatile	ppm		< 1	ICP AES (D86 for IBP - 250 cut)	Frequency: R ⁷	CAPP Guidance. Refer to AEB Directive 058. Violating test results communicated to the AEB

Notes

- For these properties, blending should not occur.
- AR: All Receipts of MSW component streams tested using weekly composite.
- MR: Monthly Random testing of MSW component streams.
- QR: Quarterly Random testing of MSW component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018

Light Sour Blend (LSB) Pool Quality Specifications

Quality Specifications for Component Streams to the Light Sour Blend (LSB) Pool							
Quality	Units	Min	Max	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications							
Density (15C)	kg/m ³	>799	<876	834	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20		ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1		H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4:1} @ 37.8 C)	kPa		95 ⁸		ASTM D6377	Frequency: MR ³	Immediate shut-in ⁵
S&W	vol%		0.5		ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1		ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typicals							
MCR	wt%		4	3.2	ASTM D4530	Frequency: MR ³	Reclassification Process ⁶
TAN	mgKOH/g		0.25	0.26	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Reclassification Process ⁶
Nickel	mg/L		11	8	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Vanadium	mg/L		20	18	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Naphtha (IBP-350F)	mass% recovered			28	ASTM D7169		
Distillate (350-650F)	mass% recovered			29	ASTM D7169		
Gas Oil (650-980F)	mass% recovered			24	ASTM D7169		
Resid (+980F)	mass% recovered			18	ASTM D7169		

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

1. For these properties, blending should not occur.
2. AR: All Receipts of LSB component streams tested using weekly composite.
3. MR: Monthly Random testing of LSB component streams.
4. QR: Quarterly Random testing of LSB component streams. Upon violation perform probational testing at Enbridge discretion.
5. Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
6. Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
7. R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
8. Max 95kPa year round, specification updated September 2018

Medium Sour Blend (MSB) Pool Quality Specifications

Quality Specifications for Component Streams to the Medium Sour Blend (MSB) Pool							
Quality	Units	Min	Max	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications							
Density (15C)	kg/m ³	>799	<876	846	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<20		ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1		H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4,1} @ 37.8 C)	kPa		95 ⁸		ASTM D6377	Frequency: MR ³	Immediate shut-in ⁵
S&W	vol%		0.5		ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1		ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typicals							
MCR	wt%		6	3.8	ASTM D4530	Frequency: MR ³	Reclassification Process ⁶
TAN	mgKOH/g		0.5		ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Reclassification Process ⁶
Nickel	mg/L		33	14	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Vanadium	mg/L		75	34	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Naphtha (IBP-350F)	mass% recovered			25	ASTM D7169		
Distillate (350-650F)	mass% recovered			26	ASTM D7169		
Gas Oil (650-980F)	mass% recovered			26	ASTM D7169		
Resid (+980F)	mass% recovered			22	ASTM D7169		

**The estimated crude quality of a pool, understanding the fact that this volume-weighted average estimation is based on historical pool component quality and volume. This estimate is provided for informational purposes only.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of MSB component streams tested using weekly composite.
- MR: Monthly Random testing of MSB component streams.
- QR: Quarterly Random testing of MSB component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018

Midale (M) Pool Quality Specifications

Quality Specifications for Component Streams to the Midale (M) Pool							
Quality	Units	Min	Max	Pool Typical Ex- Cromer**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications							
Density (15C) ⁹	kg/m ³	860	890	872	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	2	<100		ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1		H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8C)	kPa		95 ⁸		ASTM D6377	Frequency: MR ³	Immediate shut-in ⁵
S&W	vol%		0.5		ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1		ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typicals							
MCR	wt%			5.2	ASTM D4530	Frequency: MR ³	Reclassification Process ⁵
TAN	mgKOH/g			0.3	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Reclassification Process ⁶
Nickel	mg/L			12	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Vanadium	mg/L			23	ASTM D5708-05	Frequency: MR ³	Reclassification Process ⁶
Naphtha (IBP-350F)	mass% recovered			20	ASTM D7169		
Distillate (350-650F)	mass% recovered			28	ASTM D7169		
Gas Oil (650-980F)	mass% recovered			26	ASTM D7169		
Resid (+980F)	mass% recovered			26	ASTM D7169		

****The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Cromer, timeframe May 2016 – May 2017.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of M component streams tested using weekly composite.
- MR: Monthly Random testing of M component streams.
- QR: Quarterly Random testing of M component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018
- Density range effective October 1, 2017.

Premium Conventional Heavy (PCH) Pool Quality Specifications

Quality Specifications for Component Streams to the Premium Conventional Heavy (PCH) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications								
Density (15C)	kg/m ³	≥904	≤940			ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	≥100	≤350			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8C)	kPa		95 ⁹			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical								
Resid (+980F)	mass% recovered			≤39	41	ASTM D7169	Frequency: MR ³	Notification Process ⁶
TAN ⁹	mgKOH/g		≤1.1	<0.9	0.9	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Reclassification Process ⁶
Nickel	mg/L			<60	47	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Vanadium	mg/L			<130	111	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Deemed Butane	vol%			<3	2.9	ASTM D7169	Frequency: MR ³	Notification Process ⁶

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of PCH component streams tested using weekly composite.
- MR: Monthly Random testing of PCH component streams.
- QR: Quarterly Random testing of PCH component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018
- Heavy High TAN Crude: TAN > 1.1 mgKOH/g
Heavy Crude: TAN ≤ 1.1. mgKOH/g

Conventional Heavy (CHV) Pool Quality Specifications

Quality Specifications for Component Streams to the Conventional Heavy (CHV) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications								
Density (15C)	kg/m ³	≥904	≤940			ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	≥100	≤350			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8 C)	kPa		95 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical								
Resid (+980F)	mass% recovered			>39	41	ASTM D7169	Frequency: MR ³	Notification Process ⁶
TAN ⁹	mgKOH/g		≤1.1	<1.1	1.1	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Reclassification Process ⁶
Nickel	mg/L			<70	45	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Vanadium	mg/L			<160	107	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Deemed Butane	vol%			<3	2.5	ASTM D7169	Frequency: MR ³	Notification Process ⁶

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of CHV component streams tested using weekly composite.
- MR: Monthly Random testing of CHV component streams.
- QR: Quarterly Random testing of CHV component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018
- Heavy High TAN Crude: TAN > 1.1 mgKOH/g
Heavy Crude: TAN ≤ 1.1 mgKOH/g

Kearl Heavy Dilbit (KDB) Pool Quality Specifications

Quality Specifications for Component Streams to the Kearl Heavy Dilbit (KDB) Pool							
Quality	Units	Min	Max	Typical*	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications							
Density (15C)	kg/m ³	≥904	≤940	925	ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	≥100	≤350		ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1		H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8 C)	kPa		95 ⁸	56	ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5		ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1		ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical							
MCR	wt%			8.79	ASTM D4530	Frequency: MR ³	Notification Process ⁶
TAN	mgKOH/g			2.0	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Notification Process ⁶
Nickel	mg/L			48	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Vanadium	mg/L			128	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Other Requirements							
● Production method: Mined							

*The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

1. For these properties, blending should not occur.
2. AR: All Receipts of KDB component streams tested using weekly composite.
3. MR: Monthly Random testing of KDB component streams.
4. QR: Quarterly Random testing of KDB component streams. Upon violation perform probational testing at Enbridge discretion.
5. Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
6. Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
7. R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
8. Max 95kPa year round, specification updated September 2018

Synbit Blend (SYB) Pool Quality Specifications

Quality Specifications for Component Streams to the Synbit Blend (SYB) Pool								
Quality	Units	Min	Max	Typical*	Pool Typical Ex- Superior**	Referee Test Method	Test Frequency	Enbridge Response to Crude Not Meeting Quality Specs
Existing Specifications								
Density (15C)	kg/m ³	≥904	≤940			ASTM D4052	Frequency: AR ²	Delayed shut-in ⁶
Viscosity	cSt	≥100	≤350			ASTM D7042	Frequency: QR ⁴	Delayed shut-in ⁶
Olefins, total ¹	mass%		<1			H NMR	Frequency: R ⁷	Immediate shut-in ⁵
Vapour Pressure (VPCR _{4.1} @ 37.8 C)	kPa		95 ⁸			ASTM D6377	Frequency: QR ⁴	Immediate shut-in ⁵
S&W	vol%		0.5			ASTM D4007	Frequency: AR ²	Immediate shut-in ⁵
Organic Chlorides ¹	wppm		<1			ASTM D4929	Frequency: QR ⁴	Immediate shut-in ⁵
Component Typical								
MCR	wt%			<9	7.5	ASTM D4530	Frequency: MR ³	Notification Process ⁶
Naphtha (IBP-350F)	mass% recovered			7-14	9	ASTM D7169	Frequency: MR ³	Notification Process ⁶
Resid (+980F)	mass% recovered			29-38	32	ASTM D7169	Frequency: MR ³	Notification Process ⁶
TAN	mgKOH/g			>1.1	1.7	ASTM D664 & ASTM D664 CCQTA modified	Frequency: MR ³	Notification Process ⁶
Nickel	mg/L			<65	45	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Vanadium	mg/L			<172	117	ASTM D5708-05	Frequency: MR ³	Notification Process ⁶
Other Requirements								
– Only the following approved Light Synthetics to be utilized as diluent for SYB feeder components. These include OSA, SSP, PAS, CNS, PSC, HSB, SYN, PSY, HSC, and any combination thereof. – Within New Commodity Approval process, a raw bitumen assay is to be submitted.								

*The expected or anticipated crude quality of individual components, understanding the fact that there may be, on occasion, variability outside of the range of the typical.

**The estimated crude quality of a pool is based on a limited number of random composite samples of batches ex-Superior, timeframe May 2016 – May 2017.

Notes

- For these properties, blending should not occur.
- AR: All Receipts of SYB component streams tested using weekly composite.
- MR: Monthly Random testing of SYB component streams.
- QR: Quarterly Random testing of SYB component streams. Upon violation perform probational testing at Enbridge discretion.
- Immediate shut-in upon identifying violation. Request third party Certificate of Analysis prior to subsequent receipt.
- Upon violation, notification to applicable party, increase monitoring. Consequence based on outcome of increased monitoring.
- R: Random testing. 2015 – Twice per year; 2016 onwards – Annually.
- Max 95kPa year round, specification updated September 2018